

MODEL SR 9000

APPLICATIONS

- > The SR 9000 Industrial Extra Heavy Duty Insulated Traffic Door is designed for use in places where man-ridden vehicles are used to transport goods from one area to another.
- > Good for all pedestrian, cart or motorised man-ridden traffic in dry storage, refrigerated or washdown environments.

LIMITATIONS

- > The SR 9000 is good for the heaviest of applications. Put this door to the test!

FEATURES & ADVANTAGES

- > All SR 9000 doors feature a patent pending molding construction with a 1/8" ABS outer skin that will retain its physical properties to -40° F/C. They are available in six popular colours.
- > The SR 9000 door body is impervious to moisture, acid, petroleum products, animal fats, rodents, insects and salt solutions.
- > The hollow shells are injected with a high-density non-CFC urethane core that provides stability and superior insulating qualities, making them ideally suited for walk-in cooler applications. It also gives them soundproofing qualities proven to reduce noise levels
- > SR 9000 doors are known for their lightweight and indestructible construction, as well as their ease of maintenance and long service life. This allows them to open easily, operate smoothly and allow for safe, damage-free passage of personnel and equipment.
- > Perimeter edges are bull-nosed with a minimum 5/16" radius to prevent



excessive wear on the edges. Replacement of gasketing is simple and easily done on site.

- > Standard vision panels are available in many sizes based on door panel width. They are made of a 1/8" clear polycarbonate sheet that is scratch resistant and UBC compatible. Windows can be mounted in any location on the panel *upon request* and will conform to ADA requirements. Double pane vision panels for use in refrigerated areas are also available *upon request*.
- > All SR 9000 Insulated Impact Traffic Doors operate on the CMI type 'V' Gravity Hinging System complete with bottom hinge pin assembly.

OPTIONS & COLOURS

- > Optional cross-linked polyethylene spring bumpers, impact plates, partial edge gasketing and lower hinge guards are available. All add years of life to your door without compromising the fit and finish.
- > The SR 9000 is available in your choice of standard colours that include gray, blue, red, black. Optional colours and colour matches are available on request.

INSTALLATION & MAINTENANCE

- > The SR 9000 Series are conveniently packaged ready to install upon delivery in existing of factory supplied frames. Easy-to-follow instructions and thread-forming fasteners are included in every package.
- > These doors require only periodic cleaning with an industrial soap or detergent. Regular lubrication of the moving parts is recommended.

WARRANTY

- > A three-year hinging system warranty and a one-year warranty against door panel breakage is offered on SR 9000 Industrial Doors subjected to worker-ridden vehicle traffic with the use of bollards. All warranties stipulate correct installation and sizing requirements.
- > For forklift operation, the width of the opening must be a minimum 36" wider than the widest load going through the opening, and the wider the better. We recommend 96" to 120" openings for forklift use.



Renowned for their lightweight construction of durable material and a long service life, CMI Insulated Series Doors are a “must-have” for many companies. Ideal for dry storage, refrigerated, or wash down environments, this door has been designed to handle the toughest abuse.

With a patent pending construction and 1/8” outer skin, the door retains its physical properties to -40° F and is impervious to moisture, acid, petroleum products, animal fats and salt solutions. CMI Insulated Series Doors open easily, operate smoothly and close under their own weight allowing for safe damage-free passage of personnel and equipment.

FEATURES:

- > Internal welded steel perimeter with corner gussets
- > 1 7/8” hollow shells foamed in place with high density non-CFC urethane foam core
- > Soundproofing and insulating qualities
- > PVC bull-nosed with key gasket edge extrusion fastened to internal steel
- > 1/8” clear polycarbonate standard vision panels set in vacuum-formed frames
- > Stainless steel “V” cam hardware
- > USDA compliant
- > Ag Canada accepted

SR 9000 FX series:

- > Same as above with added internal steel reinforcements and corner gussets for man-ridden forklift traffic.

INSULATED DOORS:

MEDIUM TO HEAVY TRAFFIC:

(Pedestrians to motorized pallet jack traffic).

All doors 1 7/8” thick famed in place with PVC bull-nose perimeter edging, CMI HD “V” cam hardware and vacuum-formed vision panels.

- > Washdown: yes
- > SR 9000: 1/8” ABS face sheets
- > SR 9000 SS: Stainless steel face sheets
- > SR 9000 GV: Galvanised face sheets

HEAVY TRAFFIC:

(Pedestrian to man-ridden forklift traffic).

All doors 1 7/8” thick foamed in place with added internal reinforcing, PVC bull-nose perimeter edging, CMI HD “V” cam hardware and vacuum formed vision panels.

- > Washdown: Yes
- > SR 9000 FX: 1/8” ABS face sheets
- > SR 9000 FX SS: Stainless steel face sheets
- > SR 9000 FX GV: Galvanised face sheets.

VISION PANELS:

Vision panels
pane or optional following sizes:

- > ° 410 X 510 Standard size

ABS STANDARD COLOURS:



red



burgundy



beige



montana blue



metallic gray



charcoal gray



black

